

**SPECIFICATIONS FOR SIDE FAN DESIGN**
**SPECIFICATIONS FOR FAN UNDER DESIGN**

<b>MODEL FAN UNDER DESIGN</b>	<b>BPH DRY &amp; COOL WHEAT 5 POINTS</b>	<b>BPH DRY &amp; COOL WHEAT 10 POINTS</b>	<b>FAN UNDER DESIGN No. of FANS</b>	<b>FAN UNDER DESIGN HP</b>	<b>BU TOTAL HOLDING</b>	<b>LEVELLING AUGER FILL HEIGHT</b>	<b>LEVELLING DRAG FILL HEIGHT</b>	<b>GRAVITY FILL HEIGHT</b>
800-10	540	350	2	15	700	32	34	34
800-16	800	520	2	20	1000	44	46	46
1600-8	900	590	4	20	1178	28	30	32
1600-10	1085	705	4	30	1400	32	34	36
1600-12	1260	820	4	30	1625	36	38	40
1600-14	1400	930	4	30	1848	40	42	44
1600-16	1638	1000	4	40	2072	44	46	48
1600-18	1780	1157	4	60	2296	48	50	52
1600-20	2000	1260	4	60	2520	52	54	56
1600-22	2130	1380	4	60	2744	56	58	60
2400-8	1368	880	6	30	1764	28	30	34
2400-10	1630	1050	6	45	2100	32	34	38
2400-12	1890	1220	6	45	2436	36	38	42
2400-14	2150	1390	6	45	2772	40	42	46
2400-16	2410	1560	6	60	3108	44	46	50
2400-18	2669	1730	6	90	3444	48	50	54
2400-20	2930	1900	6	90	3780	52	54	58
2400-22	3192	2070	6	120	4116	56	58	62
2400-24	3450	2245	6	120	4452	60	62	66
3200-18	3562	2315	8	120	4594	N/A	50	56
3200-20	3910	2530	8	120	5043	N/A	54	60
3200-22	4255	2766	8	160	5490	N/A	58	64
3200-24	4605	2990	8	160	5939	N/A	62	68
3200-26	4950	3218	8	160	6386	N/A	66	72
4000-22	5316	3456	10	200	6860	N/A	58	N/A
4000-24	5752	3738	10	200	7420	N/A	62	N/A
4000-26	6184	4020	10	200	7980	N/A	66	N/A
4800-22	6380	4146	12	240	8232	N/A	58	N/A
4800-24	6902	4486	12	240	8904	N/A	62	N/A
4800-26	7422	4825	12	240	9576	N/A	66	N/A